



ELECTRONIC SOUNDER


A versatile 24V electronic sounder for use in a wide range of applications.

Sound signals may be set in 3 ways; continuous, intermittent or warble.



SPECIAL FEATURE

'Squashni' sounders are useful for small rooms such as Halls of Residences. They may be used with a detector which reduces the number of fixing points or as a standalone sounder with a cover plate.



ORDER CODES

Multitone Low Profile sounder, Red with shallow base	74451-24NM
Multitone Low Profile sounder, White with shallow base	74451-55NM
Multitone Low Profile sounder, Red with deep base	74452-24NM
Multitone Low Profile sounder, White with deep base	74452-55NM
Sounder base, white 3 tone	74456-24NM
Sounder base cover plate	74456-61NM
Bedhead sounder	74455-24NM

TECHNICAL SPECIFICATION

Type	Shallow Base	Deep Base	Bedhead	Sounder Base
IP Rating	IP54	IP65	IP54	IP54
Approximate Weight	0.24kg	0.26kg	0.11kg	0.15kg
Operation	Continuous	Continuous	Continuous	Continuous
Operating Voltage Range	9-28V d.c.	9-28V d.c.	9-28V d.c.	9-28V d.c.
Typical Sound Output @ 1m, 12V d.c.	93dBA	93dBA	94dBA	87dBA
Typical Sound Output @ 1m, 24V d.c.	100dBA	100dBA	97dBA	93dBA
Current Consumption	8mA @ 12V, 18mA @24V			
IP Rating	IP54	IP65	IP54	IP54
Ambient Temperature	-25°C to +70°C			

DIMENSIONS (mm)

